



Angled handrail 35/35cm UKU

- Smooth edges to prevent accidental catching and injury
- Maximum lifting capacity of 180 kg
- Made of white powder-coated carbon steel
- An anti-corrosion layer
- Mounting kit included
- Silicone pads leveling unevenness
- Easy to clean
- Certificate of the Polish Institute of Hygiene
- CE declaration of conformity
- National Declaration of Performance

Material	Carbon steel
Finish	Powder-coated in white
Type of coating	Polyester paint
Coating thickness	120 μ
Dimensions	350x350 mm
Tube diameter	Ø 25 mm
The wall thickness	1,5 mm
Maximum load	180 kg
Hole diameter	Ø 6,5 mm
Number of fixing holes	4
Includes	6x70 mm screws, 8x65 mm plugs

Angled handrail made of white powder-enamelled carbon steel (anti-corrosion primer was used for enamelling). The 350x350 handrail is intended for wall mounting in the bathtub area. The diameter of the tube used in the production is 25 mm, while the wall thickness is 1.5 mm. The maximum load capacity of the railing is 180 kg. Each handrail comes with a mounting kit (which includes, among others, screws, silicone washers, wall plugs, plugs), as well as a user manual and a warranty card. The offered handrails are certified by the Polish Institute of Hygiene, CE Declaration of Conformity and the National Declaration of Performance.