



Time battery 9073

- The body is made of chrome-plated brass
- Two variants: 9030 and 9073AB with an anti-block system
- Water flow time adjustment (available for 9073)
- Water pressure reduction in the form of a cup and water flow reducer
- High resistance to vandalism (the 9073AB variant has additional protection in the form of an anti-block system)
- Classic pattern
- Exceptional durability and reliability
- The product is entirely made in the European Union
- Simple operation
- Easy to assemble
- Certificate of the Polish Institute of Hygiene
- CE declaration of conformity
- National Declaration of Performance

Option	For mixed water
Connector	G1/2
Design	Chrome-plated brass
Water time flow	Adjustable from 10 seconds \pm 3 second
Start	By means of the button
Water pressure reductor	up to 6l / min.
Water temperature	5-65°C
Water pressure	Min 0,5 bar - Max 6 bar (Recommended 2-4 bar)
Contains	Battery, mounting kit for the washbasin



Washbasin, wall-mounted, cold or mixed water timer. Used in rooms with pre-mixed water supply. The modern design makes the tap ideal for high-standard places. The 9073 faucet is made of chrome-plated brass and has one G1 / 2 connection.

A single outflow of water at the start of the flow takes about 10 seconds \pm 3 seconds (at a water pressure of 3 bar), and the amount of water used is about 6 l / m. The minimum connection pressure is 0.5 bar, the maximum is 6 bar. It is worth adding that the recommended connection pressure should be 2-4 bar. The offered 9073 tapered battery is available in two variants:

- 9073 universal variant, equipped with one 1/2 connection and a cup, water flow reducer and regulation hole;
- 9073AB variant with built-in anti-block system, which includes cup and flow reducer.