



Mixer 8135MIX

- Exceptional durability and reliability
- The product is made in the European Union
- Simple operation
- Easy to assemble
- Vandal-resistant finish
- Water pressure adjustment

Option	With mixer
Connector	2 x 1/2
Design	Vandal-resistant - chrome-plated brass
Water time flow	Adjustable from 15 seconds
Start	By means of the button
Water pressure reductor	up to 6l/min.
Spout	Equipped with an aerator

The wall-mounted faucet is equipped with two G1/2" connections designed for hot and cold water supply. Temperature regulation is conveniently controlled via a knob, allowing precise adjustment of operating parameters. The device features a built-in pressure reducer that stabilizes water flow, ensuring comfortable use regardless of installation conditions. The faucet is equipped with a swivel spout, enhancing its functionality and allowing easy direction of the water stream. The faucet's construction is vandal-resistant, made from high-quality materials that are resistant to mechanical damage, making it an ideal solution for locations with increased risk of damage.

A single water flow from the faucet, at standard settings, lasts approximately 15 seconds at a working pressure of 3 bar. The water flow rate is approximately 6 l/min at 3 bar pressure. The connection pressure can vary between 1 and 5 bar, although a pressure range of 2-4 bar is recommended.

The 8135MIX faucet comes with an installation kit, as well as filters and check valves. Moreover, the entire product holds certification from the Polish Institute of Hygiene, a CE Declaration of Conformity, and a National Declaration of Performance.