



Angular horizontal handrail for shower 80/80cm UK8

- Smooth edges to prevent accidental catching and injury
- Maximum lifting capacity of 180 kg
- Made of carbon steel
- White color
- Silicone pads leveling unevenness
- Mounting kit included
- Easy to clean
- Certificate of the Polish Institute of Hygiene
- CE declaration of conformity
- National Declaration of Performance

Material	Carbon steel
Finish	Powder coated in white
Type of coating	Polyester paint
Coating thickness	120 μ
Handrail type	Angular horizontal shower
Handrail length	800x800 mm
Tube diameter	\varnothing 25 mm
The wall thickness	1,5 mm
Maximum load	180 kg
Hole diameter	\varnothing 6,5 mm
Number of fixing holes	12
Includes	3.5x60 mm screws, 10x60 mm plugs

Angled, horizontal, shower handrail for the disabled, mounted on the wall. The offered handrail is made of white powder-coated carbon steel. The tube used for production has a diameter of 25 mm, and the wall thickness is 1.5 mm. The dimensions of the UK8 handrail are 800 x 800mm, while its maximum load capacity is 180 kg. It is designed for wall mounting with four flanges. Moreover, the prepared handrail for the disabled has smooth edges, which means that its construction eliminates the risk of accidental catching or injury.

Each handrail comes with a mounting kit (which includes, among others, screws, washers, wall plugs, plugs), as well as a user manual and a warranty card. The offered handrails are certified by the Polish Institute of Hygiene, CE Declaration of Conformity and the National Declaration of Performance.

