



Right horizontal and vertical handrail 80/80/1100 cm 32-UKKP

- Smooth edges to prevent accidental catching and injury
- Maximum lifting capacity of 180 kg
- Made of white powder-coated carbon steel
- An anti-corrosion layer
- Mounting kit included
- Silicone pads leveling unevenness
- Easy to clean
- Certificate of the Polish Institute of Hygiene
- CE declaration of conformity
- National Declaration of Performance

Material	Carbon steel
Finish	Powder-coated in white
Type of coating	Polyester paint
Coating thickness	120 μ
Handrail type	Shower handrail angular left
Handrail length	800x800x1100 mm
Tube diameter	Ø 32 mm
The wall thickness	1,5 mm
Maximum load	180 kg
Hole diameter	Ø 6,5 mm
Number of fixing holes	8

Handrail for disabled people, angular, right, made of carbon steel enameled with white powder (with anti-corrosion layer). The angular handrail, dimensions 800/800 / 1100mm, is intended for wall mounting in the shower area.

The diameter of the tube used in the production is 32 mm, while the wall thickness is 1.5 mm. The maximum load capacity of the railing is 180 kg. Moreover, the prepared handrail for the disabled has smooth edges, which means that its construction eliminates the risk of accidental catching or injury.

Each handrail comes with a mounting kit (which includes, among others, screws, silicone washers, wall plugs, plugs), as well as a user manual and a warranty card. The offered handrails are certified by the Polish Institute of Hygiene, CE Declaration of Conformity and the National Declaration of Performance.