



## Hand dryer

- Comfortable access, ease of use for everyone
- Fast, average drying time in 10 seconds
- Low power consumption, consumes only 2.25 Watt per cycle
- Durable, vandal-resistant construction made of stainless steel.
- The air flow can be adjusted
- Small dimensions

Housing	Stal nierdzewna AISI 304
finish	white
Action	For photocell
Dimensions	360 x 490 x 190/250 mm
Tension	220 - 240 V, 50 Hz
Total power	500 - 1100 W
Heater power	-
Revolutions per minute	23 400
Volume level	75 - 81 dB
Air flow	3000 - 4020 l/min. (180 - 241m <sup>3</sup> /h)
Air velocity	403 - 534 km/h
Energy class	IP24
Standards	CE, TÜV-GS, EMV, EMC, EMF, ICIM, UL, PCT, RoHS, REACH, WEEE, PAH/ZEK
Warranty	2 YEARS

Ultra fast drying. In just 10 seconds

The latest hand dryer model, thanks to its unique tubular structure with microdozzles, ensures hand drying in a few seconds. The new air supply system via micro-nozzles allows you to place your hands in a horizontal position. It is designed to quickly "micronize" water droplets so as to minimize drop falling to the floor, and not as it is the case with other vertical drying systems. The hand drying system installed at a height of 110cm makes it easier for anyone to use even the disabled.

