




Tap hand dryer 3 in 1 MAS2

- Stylish and modern design IPX4 protection
- Automatic shutdown after 60 seconds of continuous use
- Intelligent sensor
- Top-quality housing, made of brass
- High-pressure rotation of the air stream causes immediate removal of water drops from the hands
- Environmentally friendly
- Easy and quick disinfection

Housing	Brass
Finish	Matt
Action	Photocell
Dimensions	360 X155 X205 mm
Tension	220 – 240 V, 50/60 Hz
Total power	1000 W
Volume level :	75 dB
Blow-out temperature	up to 33 °C
Air flow	288 km/h
Energy class :	IPX4



The countertop hand dryer with a built-in photoelectric sensor and liquid soap dispenser is a product most commonly used in large public restrooms. The offered set is made of brass with IPX4 protection. The rated power of the presented hand dryer is 1000W, with an air blow speed of up to 288 km/h. The drying time per use is 15-20 seconds (after which the dryer automatically shuts off), with the air temperature reaching up to 33°C. The noise level of the dryer does not exceed 75 dB. For the built-in battery, the water consumption rate is approximately 6 liters per minute, with a water inlet pressure of 3 bar. The inlet pressure can range from 0.5 to 6 bar, but the recommended inlet pressure is between 2-4 bar. Additionally, the water connection is 1xG1/2&HASH39;.